FINISH Black Ano. Bronze Ano. Clear Ano. WiM Std. White Pt. WiM Std. Black Pt. Other												
SERIES:	TRIM			DOOR SEAL	RATING	S	STRIKE TYPE					
315 = 3-3/4"	30	2 = 1" X 3/8"		Black Vinyl	NON RATED			ASA (4-7/8")				
318 = 4-7/8"	30	4RM = 1-1/2"	Black Mohair		20 MIN. (LPE)			CYL (2-3/4")				
319 = 5-0/0"	30	4-2 = 2" X 5/1	6"	Gray Vinyl		20 MIN. (LMF) Electric Strike Pre				Strike Prep		
				Gray Mohair		20 MI	MIN. (LVT) No Strike Prep Required					
				White Vinyl		90 MII	N. PP	Ē	RIM Pa	nic Block		
DOOR FRAM	E - SING	LE		White Mohair								
LH FRAME QTY:] _/						A				
		لى		_								
MARK #		-		Standard Prep Informati	on:	Î		st 🕇 🕇				
			-	4-1/2" Standard Weight Hi	inges	· · ·						
			-	and 4-7/8" ASA strike pl Black Vinyl	ate			2nd	STK			
			-	Rough Opening Informat	ion			<u> </u>				
RH FRAME QTY:				Width = ID (A) + 1-1/2		B	∣┫	3rd				
MARK #			L	Height = ID (B) + 3/4'					.	center l	ine of strike plate	
				Extended lip strike requi with 1-1/2" and 2-0/0" Flush				V				
			_				1	4t	h			
			_					Ļ	<u>,</u>			
Special Instructions												
				ID frame to finish floor		•						
					SCRIBE							
[Use Western Standard Hinge					OCATIONS		STRIKE C/L	
	A	В	S	and Strike Locations	;	1st Hinge	2nd Hin	ge 3rd	Hinge	4th Hinge	STK	
				YES NO								
Western Integrated Materials, 3310 E. 59th Street	Inc. O	CUSTO	MER:		DATE:			PAGE		EL	ELEVATION	
Long Beach, CA 90805		ORDER		R		REVISED:						
Phone: 562.634.2823 Fax: 562.790.6903	aa. Thad	JOB NA										
AluminumDoorFrames.com		PURCH	PURCHASE ORDER:									